



Specifications

Item -	34126B
Model -	LED2.5CTC/FIL/27K/D
Bulb Shape -	B11
Bulb Type -	Filament LED
Beam Spread -	360 Degrees
Input Voltage -	AC 120
Watts -	2.5W
Base Type -	E12
Base Material -	Nickel Plated Brass
Diameter -	1.377 Inches
Height -	4.05 Inches
Color Temp -	2700K
CRI -	80
Lumen -	180
Finish -	Clear
Dimmable -	Yes
UL Rating -	Suitable for Dry or Damp Locations
Enclosed Rated -	No
Life -	15,000 Hours

Caution

- Use only on 120 Volt 60Hz circuits. This device is not intended for use with emergency exit fixtures or emergency lights.
- This lamp is not compatible with all dimmers. During installation, ensure that the power is switched off prior to connecting or disconnecting the lamp from the fixture.
- No user serviceable parts inside. To avoid electrical shock, do not disassemble the product.
- To prevent injury or property damage from falling lamp, only use in fixtures that can structurally support this lamp.
- The condition of the lamp holder can affect the life hours of a bulb. Inspect the lamp holder regularly for deterioration. If deterioration has occurred, replace the lamp holder immediately before continuing operation.

Precaución

- Use solo en circuitos de 120 voltios 60Hz. Este dispositivo no está diseñado para su uso con dispositivos de salida de emergencia o luces de emergencia.
- Esta lámpara no es compatible con todos los atenuadores. Durante la instalación, asegúrese de que la alimentación esté desconectada antes de conectar o desconectar la lámpara del dispositivo.
- No hay piezas reparables por el usuario dentro. Para evitar descargas eléctricas, no desarme el producto.
- Para evitar daños o daños a la propiedad por la caída de la lámpara, solo use accesorios que puedan soportar estructuralmente esta lámpara.
- La condición del portalámparas puede afectar las horas de vida de una bombilla. Inspeccione el portalámparas regularmente para ver si está deteriorado. Si se produce un deterioro, reemplace el portalámparas inmediatamente antes de continuar con la operación.