



### Specifications

Item	- 35692C
Model	- LED Emergency Combo - Square Wet Locations
Wattage	- 1.2 Watts Per Head
Voltage	- 120/277VAC 60 Hz
Listings	- UL Listed
Dimmable	- No
Height	- 13.2 inches (336.55mm)
Width	- 2.75 inches (69.85)
Length	- 12.5 inches (317.5mm)
Ambient operating temp.	- 32°F to 104°F (0°C to 40°C)
Housing	- Thermoplastic
Battery	- Ni-MH 3.6V 1200 MAH
Installation Type	- Wall or End
Battery Life	- ≥ 90 minutes

### Caution

- May be used outdoors under cover.
- Equipment should be mounted in locations and at heights where it will not be subject to tampering by unauthorized personnel.
- Do not mount near gas or electric heaters
- The use of accessory equipment that is not recommended by the manufacturer may cause an unsafe condition.
- Do not use this equipment for other than its intended use.
- Installation and servicing of this equipment should be performed by qualified personnel.
- Disconnect AC power before servicing
- Use caution when servicing batteries. Battery acid can cause burn to skin or eyes, If acid is spilled on skin or eyes flush acid with fresh water and contact a physician immediately.
- Suitable for wet locations.

### Precaución

- Se puede usar al aire libre bajo techo.
- El equipo debe montarse en ubicaciones y alturas donde no estará sujeto a manipulación por personas no autorizadas personal.
- No lo monte cerca de calentadores de gas o eléctricos.
- El uso de equipos accesorios que no se recomiendan por el fabricante puede causar una condición insegura
- No use este equipo para otro uso que no sea el previsto.
- La instalación y el mantenimiento de este equipo deben ser realizados por personal calificado.
- Desconecte la alimentación de CA antes de realizar el mantenimiento.
- Tenga precaución cuando repare las baterías. El ácido de la batería puede causar quemaduras a la piel u ojos, si se derrama ácido sobre la piel o los ojos, enjuague el ácido con agua y contacte a un médico inmediatamente.
- Apto para lugares húmedos.

