

LED FULL CUT-OFF WALLPACK

WALLPACK 36-48-60W 3CCT

Specifications

Item - 37320D

| | Model - LED FULL CUT-OFF WALLPACH |
|--|---|
| | Bulb Type - LED |
| | Input Voltage - 120-277VAC 50/60Hz |
| | Watts - 36W/48W/60W SELECTABLE |
| | Color Temp - 3K/4K/5K SELECTABLE |
| | CRI - >80 |
| | Lumen - 4680-6240-7800 |
| | Dimmable - Yes, 0-10V |
| | UL Rating - Suitable for Wet Locations |
| | Length - 14.20" (360.8 mm) |
| | Width - 6.02" (153mm) |
| | Height - 9.27" (235.5mm) |
| | Ambient Operating Temp40°F to 113°F (-40°C to 45°C) |
| | Finish - Bronze |
| | Life - 50,000 Hours |

Surge Protection - 4KV

Average Beam Angle - 110°H x 90° V

Photocell - Optional (37381G)

Note

Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage, and/or product malfunction.

This luminaire is designed to be horizontally mounted with the LEDs facing down.

the World

This product is not suitable for several special environments, such as places with corrosive gas, liquids, or high pressure water vapor. Suitable for wet locations.

Warning

PLEASE READ ALL INSTRUCTIONS BEFORE ATTEMPTING INSTALLATION

- This fixture must be wired in accordance with the national electrical code and applicable local codes and ordinances.
- To prevent personal injury or product damage only licensed electricians should install.
- To avoid electric shock or component damage disconnect power before attempting installation or servicing.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- RISK OF PERSONAL INJURY- Fixture may become damaged and/or unstable if not installed properly.

