

38677A	LED33T8/835/8FT/DR/SS FA8	33W	35K	4400 Lumens
38678A	LED33T8/841/8FT/DR/SS FA8	33W	41K	4400 Lumens
38679A	LED33T8/850/8FT/DR/SS FA8	33W	50K	4400 Lumens
38680A	LED33T8/865/8FT/DR/SS FA8	33W	65K	4400 Lumens

LED Fluorescent Direct Replacement

50,000 Avg Life Hours
 4400 Initial Lumens
 Direct Replacement
 Fa8 Single Pin Base Type
 T8 Bulb Shape
 3500-6500K Kelvin
 82 CRI
 33 Watts
 120-277 Volts
 Beamspread 120°
 Safe-Shield®



- LONG LIFE
- ENERGY EFFICIENT
- ROHS COMPLIANT
- NO MERCURY NO LEAD
- ZERO UV DYE AND PIGMENT FADE
- 3000 - 6500K 82 CRI.
- UL CERT DR.
- 96 in. NOMINAL LENGTH.
- NOT FOR OUTDOOR USE.
- MIN. AMBIENT OPERATING TEMP. -4°F. -20°C.
- MAX. AMBIENT OPERATING TEMP. 113°F. 45°C.
- NOT COMPATIBLE WITH LOW POWER FACTOR BALLASTS
- DESIGNED TO RUN ON INSTANT START AND PROGRAMMED START BALLASTS.



Diameter:
 1.18 in.
 (29.97 mm.)

Max Overall Length: 93.75 in. (2,381.25 mm.)

